

Desiccant Dehumidifiers



Applications:

- Mold/Fungus Protection
- Surface Preparation and Coating
- Restoration Drying
- Corrosion Prevention
- Electronics Protection
- Power Plant Lay-Up
- Pharmaceutical
- Candy Manufacturing

PRODUCT FEATURES

- Main Power Phase Monitors
- 30% Inlet Air Filters
- Round Duct Collars
- 12 inches External Static Pressure
- Non-rusting Aluminum Construction
- Lightweight/Small Footprint
- Simple, Reliable Operation



TECHNICAL DATA

Dehumidifier	Model	OCD-1000	OCD-2500	OCD-5000
	Process Air Flow	1000 CFM	2500 CFM	5000 CFM
	Reactivation Heat Source	13.5kW Electric	50kW Electric	99kW Electric
	Total Static Available	2 inch WC	5 inch WC	12 inch WC
Dimensions	Length	70"	8'	12' 11.5"
	Width	32"	6.5'	6'6"
	Height	38"	6'	6'
	Weight	525 lbs	2,600 lbs	3,200 lbs
Electric	Volts	240	480	480
	Phases	1	3	3
	Hz	60	60	60
	FLA	74 FLA	90 FLA	140 (175 amp breaker)
Included Options	Transportation	Castors and fork pockets	Fork pockets	Fork pockets
	Dual Reactivation	Electric	LP gas and electric	LP gas and electric
	Connection Type	Cord	Cam-lock	Cam-lock
	Outlet Size	10"	19.75"	19.75"