



400,000 to 3.5 Million BTU Direct Fired Heaters

Applications:

- Job Site/Construction Heat
- General/Building Heat
- Temporary Shelter
- Industrial Heat
- Commercial/Institutional Heating

PRODUCT FEATURES

Body Construction Stainless Steel
 Burner Stainless Steel
 Consumption Rating High Efficiency
 Fuel Type Natural Gas/LPG Fired
 Sizes 400,000 to 3,500,000 BTU



TECHNICAL DATA

Model	Output	Manifold Pressure	Max Gas Consumption	CFM	Electrical	Weight	Dimensions
400K	High 400,000 BTU Low N/A	2" W.C. LPG 7" W.C. NG	4 Gallons/hr 400 CFH	2800	1/4 hp motor 120V, 3 amps	90 lbs	16"W x 24"H x 52"L
700K	High 700,000 BTU Low N/A	2" W.C. LPG 7" W.C. NG	7.5 Gallons/hr 700 CFH	4500	1 hp motor 120V, 8 amps	178 lbs	22"W x 31"H x 58"L
2.0M	High 2,000,000 BTU Low 800,000	2" W.C. LPG 7" W.C. NG	20 Gallons/hr 2000 CFH	8000	1.5 hp, 120 V, 14 amps 230 V, 480 V available	355 lbs	30"W x 36"H x 63"L
3.5M	High 3,500,000 BTU Low 1,000,000 BTU	9" W.C. LPG 14" W.C. NG	35 Gallons/hr 3500 CFH	21000	5 hp, 480 V, 8 amps 5 hp, 230 V, 21 amps	540 lbs	62"W x 52"H x 180"L